

# **DIRECT**<sup>TM</sup>

WIRE & CABLE

## **DLO**

DLO is used as a heavy duty power cable. Used for portable or fixed installations, leads for motors, generators, batteries, or jumper cables. For use in renewable energy applications as well as deep well submersible pump cable. Designed for shipyard and railroad applications

- UL listed RHH/RHW-2
- Rated 2kV, 1kV RW 90
- Resistant to Ozone, sunlight, oil, grease, weather, water, chemical, and abrasion
- Rated RW90-TC (tray cable)
- MSHA, VW-1
- UL 1685
- CSA RW90, RW90-TC
- ASTM B-33, B-172



### **CONSTRUCTION:**

Flexible tin coated copper

### **INSULATION**

EPR jacket

### **TEMP RANGE**

90°C Dry, 90°C Wet

### **Stock Sizes**

Available in 250 and 500 ft reels

### **Packaging**

Coil, boxed, and shrink wrap

### **COLORS**

Stock Black



## CONSTRUCTION

GAUGE	STRANDING	O.D.	NOMINAL O.D.	AMPACITY	WEIGHT/1,000ft.
#6	61/24	0.207	0.362	104	134
#4	105/24	0.264	0.413	140	192
#2	150/24	0.314	0.489	190	248
#1	225/25	0.390	0.583	220	428
1/0	275/24	0.420	0.642	260	480
2/0	325/24	0.460	0.681	300	558
3/0	450/24	0.555	0.781	350	742
4/0	550/24	0.587	0.815	405	872



412 OAK STREET  
DENVER, PA 17517

(800) 233-3848

[www.directwireusa.com](http://www.directwireusa.com)