

## **Dura-Flex Type W Pigtails**

Dura-Flex Type W is suitable for use in industrial and mining application as well as heavy-duty service and temporary power supply. Type W is also used for motor, battery, and generator leads

- UL listed 1650
- CSA C22.2 No. 96
- cULus
- Approved by Mine Safety Health Administration for use in mining application P-07-KA150015-MSHA
- FT-1, FT-5, VW-1
- RoHS Compliant
- Listed as Type RHH, RHW, & RHW-2
- Resistant to water, flame, ozone, sunlight, grease, weather, and chemicals
- UL listed assemblies



### **CONSTRUCTION:**

#### **CONDUCTORS**

Flexible 30 gauge copper per ASTM B172

#### **INSULATION**

Flexible 30 gauge copper per ASTM B172

#### **TEMP RANGE**

-40°C to +90°C Dry. 90°C Wet Rating

#### **STOCK SIZES**

3' & 6' stock sizes

#### **PACKAGING**

Coil, boxed, and shrink wrap

#### **COLORS**

Stock black. Custom colors available



## CONSTRUCTION

AMPACITY	DESCRIPTION	LENGTH	CABLE	AMPACITY	PART No.
4/0	4/0 DF BLK 3' W/BLK M CAM & BARE	3	TYPE W	405 AMP, 2000V	TW0110
4/0	4/0 DF BLK 3' W/BLK F CAM & BARE	3	TYPE W	405 AMP, 2000V	TW0111
4/0	4/0 DF BLK 3' W/BLK M CAM & LUG	3	TYPE W	405 AMP, 2000V	TW0266
4/0	4/0 DF BLK 3' W/BLK F CAM & LUG	3	TYPE W	405 AMP, 2000V	TW0112
4/0	4/0 DF BLK 3' W/BLK M CAM & PIN	3	TYPE W	405 AMP, 2000V	TW0339
4/0	4/0 DF BLK 3' W/BLK F CAM & PIN	3	TYPE W	405 AMP, 2000V	TW0344
4/0	4/0 DF BLK 6' W/BLK M CAM & BARE	6	TYPE W	405 AMP, 2000V	TW0139
4/0	4/0 DF BLK 6' W/BLK F CAM & BARE	6	TYPE W	405 AMP, 2000V	TW0346
4/0	4/0 DF BLK 6' W/BLK M CAM & LUG	6	TYPE W	405 AMP, 2000V	TW0342
4/0	4/0 DF BLK 6' W/BLK F CAM & LUG	6	TYPE W	405 AMP, 2000V	-12
4/0	4/0 DF BLK 6' W/BLK M CAM & PIN	6	TYPE W	405 AMP, 2000V	TW0339
4/0	4/0 DF BLK 6' W/BLK F CAM & PIN	6	TYPE W	405 AMP, 2000V	TW0345

412 OAK STREET  
DENVER, PA 17517

(800) 233-3848

www.directwireusa.com

