

DIRECT™

WIRE & CABLE

SOOW

SOOW Cable is used in industrial and processing equipment, cranes, and hoists, track systems, tools, construction equipment, motors, and associated machinery, garage portable lights, battery charger and equipment exposed to oils, solvents, flame, moisture, and other electrical equipment

- Excellent Flexibility
- Rugged jacket
- Resists Solvents, Cut, Ozone, Sunlight, Grease, Oil, and Water
- Flame tests meets VW-1, FT2, and MSHA
- Custom cut lengths available
- Sequential marked
- UL Listed
- Made in the USA



CONSTRUCTION:

CONDUCTORS

30 gauge copper per UL 62

INSULATION

EPR compound UL 62

TEMP RANGE

-50° C to +90° C

STOCK SIZES

Available in 250 and 500 ft reels. Cut to 25, 50, and 100ft coils

PACKAGING

Coiled, boxed, and shrink wrap

COLORS

Black





CONSTRUCTION

GAUGE	STRANDING	O.D.	AMPACITY	WEIGHT/1,000ft.
2/3	262/.0156	1.30	95	1287
2/4	262/.0156	1.45	80	1644
4/3	165/.0156	1.13	70	913
4/4	165/.0156	1.25	60	1156
6/3	184/.0117	.97	55	641
6/4	184/.0117	1.05	45	785
8/3	67/.0156	.83	40	452
8/4	67/.0156	.93	35	557
10/3	104/30	.65	30	281
10/4	104/30	.70	25	336
12/3	65/30	.59	25	217
12/4	65/30	.64	20	261
14/3	41/30	.52	18	161
14/4	41/30	.57	15	192
16/3	26/30	.39	13	90
16/4	26/30	.42	10	107



412 OAK STREET
DENVER, PA 17517

(800) 233-3848

www.directwireusa.com